

Ponaflex

HOSE MANUFACTURING, INC.



FOOD
GRADE



PHTHALATE
FREE



UV RESISTANT



NSF51

FDA

RoHS



COMPARE TO K7300

PONABRAID WIRE

NEW

HEAVY DUTY FOOD GRADE SPIRAL STEEL WIRE & POLYESTER YARN REINFORCED HOSE

FEATURES

- ✓ Heavy Duty Suction & Discharge Hose for Food and Beverage Applications
- ✓ Spiral Steel Wire & Yarn Reinforcement for High Vacuum & Pressure Rating
- ✓ Non-Phthalate Based Food Grade Materials in Compliance with FDA & RoHS Requirements

NORMAL SPECIFICATIONS

Part Number	Nominal Size Inch	Outer Diameter Inch	Working Pressure PSI@70°F	Bend Radius In. @70°F	Standard Length Ft	Approx. Weight Lbs/Ft
S05-075TRF	3/4	1.204	225	2.5	100	0.40
S05-100TRF	1	1.460	225	3.5	100	0.49

- Note :
1. Service life may vary depending on operating condition.
 2. Working pressures are rated at 70°F, and can be affected by fittings, method of attachments, and conveying materials.
 3. Temperature Range -4°F (-20°C) to 150°F (+65°C) depending on application.
 4. Ponaflex reserves the right to modify product specifications without prior notice due to continual product improvement.
 5. Sold in standard lengths only.